

5200-Electric

Maximize your production (open-blow) with our #5200 **all-fiber** (airlock) machine, featuring a large 14 inch (35.5cm.) diameter by 18 inch (45.7cm.) long airlock. Designed for low maintenance and high production, the #5200 provides large hopper capacity and easy loading, while offering simple rugged performance. **The #5200 electric machine is intended for use in manufactured housing.**



MATERIAL PRODUCTION RATE

MATERIAL	MACHINE w/positive displacement blower lbs/hr (kg/hr)
CELLULOSE	5200 (2358)
FIBERGLASS	2300 (1043)

lbs/hr (kg/hr) rating with 150ft. (45.8m.) of 4" (10.2cm.) hose at 16ft. (4.9m.) elevation
Product density and variable blowing conditions will affect production rate.

STANDARD FEATURES AND BENEFITS

Mechanical

- Modular component design for easy troubleshooting and maintenance
- Safety guards provide operator safety
- 62 cu. ft. (1.70 m³) hopper provides large capacity
- Three (3) agitators that enhance the condition of fibers
- Removable all steel airlock allows quick access to airlock for replacing seals
- Shredder assembly increases production and material conditioning
- 3 hp. Motor w/inline Gear reducer (3070 in./lb. torque) provides durable direct drive transmission for the toughest blowing materials
- Extra heavy, nickel plated #50 chain with hardened steel sprockets provides a rugged, corrosion/abrasion resistant drive system
- 7 1/2 hp. Totally Enclosed Fan Cooled motor powering a positive displacement blower to give extended life
- Check valve protection and pressure relief on the positive displacement blower



Electrical

- Operator safety/Hazard response features: pre-alarm buzzer, main disconnect/power interruption shutdown, emergency kill switch, manual override at the machine, 150 ft. (46m.) of remote control cord
- Single phase (1Ø) or three phase (3Ø) option for main input power

WEIGHT

1700 lbs. (771 kg.)

DIMENSIONS

42"W x 70"D x 82"H
(106cm. W x 178cm. D x 208cm. H)

HOPPER CAPACITY

62 cu. ft. (1.70 m³)

AIRLOCK

18" x 14" diameter (45.7cm. x 35.5cm. diameter)
Slide Out Removable Airlock
4" (10cm.) outlet for blowing hose

BLOWERS/SIZES

Positive Displacement Blower provides 220 CFM @ 5psi

OPTIONAL EQUIPMENT

Wireless remote