

# 575SHA Machine with shredder

## ANY JOB. ANY SIZE. ANY PLACE.



The 575SHA will out perform and outlast the competition. The 575SHA is an economical machine for the professional contractor. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications, with an additional shredder/agitator to ensure material conditioning and coverage.

- Fold down loading door
- Removable all steel airlock allows for quick access for maintenance
- Lightest machine in its class
- User friendly electric dashboard
- Clear polycarbonate safety guard allows for easy inspection
- Durable powder coat finish
- Double 14 amp / 2 Stage blowers
- Polyurethane flat free tires
- Built in tool holder

## AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY



### 65 Years of American Ingenuity



#### **Electric Dashboard**

LED start button - Digital hourmeter Digital voltmeter - Variable blower speed controls Recessed power supply



Dual Agitators Designed for constant material flow



Clear Safety Guard Allows for easy inspection

#### **POWER REQUIREMENT**

Single input, 30 amp 240V / 60Hz CSA/CUL/UL
Double input, 30/15 amps each / 120V / 60Hz CSA/CUL/UL
Triple input, 15 amps each / 120V / 60Hz CSA/CUL/UL
International - Double input, 230V / 50Hz CE

#### HOPPER CAPACITY

14 cu.ft. (.39m³) Loading made easy with built in adaptable tray

#### WEIGHT/DIMENSIONS

440lbs / 40.5"W x 31.5"D x 68" H 200kg / 103cm x 80cm x 157cm

#### **BLOWER SIZE**

14 amp / 2-Stage (120V) Double blower system - Each yields 140CFM @ 3.5 PSI

#### AIRLOCK

14" x 10" diameter 35.5cm x 25.4cm diameter 3"(7.6cm) Outlet

#### **ACCESSORIES**

Machine includes corded remote Optional accessories sold seperately

#### MATERAL PRODUCTION RATE

**Cellulose** 2000-2160 (1100-1170)\* **Fiberglass** 800-840 (363-400)\*

\*Lbs/hr (kg/hr) rating with 150 ft. (45.8m) of 3" (7.6cm) hose at 16ft (4.8m) elevation.

#### 575 PACKAGE

Part Numbers	Description	QTY
0575SHA*	575 Machine 240V	1
H319	3" x 50' Hose	3
339A	2 ½"-3" Clamps	5
380	3" Connector	2
EXTCORD-H*	100' Extension Cord	1

#### OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
328	36" Hose Reel	1
KIT-641-12-24K	Wireless Remote	1
575MK	575 Maintenance Kit	1

\*DLA (Double input) - SHA (Single input) - TLA (Triple input) Extension cords will vary based on requirements

#### ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST