

2300 Machine

ANY JOB. ANY SIZE. ANY PLACE.



The 2300 is specifically designed for the busy contractor who is increasing their business. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications.

- Fold down loading door
- Removable all steel airlock allows for quick access for maintenance
- User friendly electric dashboard
- Clear polycarbonate safety guard allows for easy inspection
- Durable powder coat finish
- Large hopper capacity for less reloading time
- Double 14 amp / 2 stage blowers
- Optional 4 blower upgrade

AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY



65 Years of American Ingenuity



Electric Dashboard

LED start button - Digital hourmeter Digital voltmeter - Variable blower speed controls Recessed power supply



Dual Agitators
Designed for constant
material flow



Clear Safety Guard Allows for easy inspection

MATERIAL PRODUCTION RATE

Cellulose

Fiberglass

3000 (1360)*

1000 (454)*

*Lbs/hr (kg/hr) rating with 150 ft. (45.8m) of 3" (7.6cm) hose at 16ft (4.8m) elevation.

POWER REQUIREMENT

Single input, 30 amp 240V / 60Hz CSA/CUL/UL
Double input, 30/20 amps each / 120V / 60Hz CSA/CUL/UL
International - Double input, 230V / 50Hz CE
*Optional 4 blower - Single input, 50 amp / 240V / 60Hz

HOPPER CAPACITY

40 cu.ft. (1.13m³) Loading made easy with built in adaptable tray

WEIGHT/DIMENSIONS

846lbs / 32.5"W x 68"D x 71"H 384kg / 83cm x 173cm x 180cm

BLOWER SIZE

14 amp / 2-Stage (120V) Double blower system - Each yields 140CFM @ 3.5 PSI

AIRLOCK

16" x 12" diameter 40.6cm x 30.5cm diameter 3"(7.6cm) Outlet

ACCESSORIES

Machine includes corded remote Optional accessories sold seperately

2300 PACKAGE

Part Numbers	Description	QTY
2306SH*	2300 Machine 240V	1
H319	3" x 50' Hose	3
339A	2 ½"-3" Clamps	5
380	3" Connector	2
EXTCORD-H*	100' Extension Cord	1

OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
328	36" Hose Reel	1
KIT-641-12-24K	Wireless Remote	1
2300MK	2300 Maintenance Kit	1

*DL (Double input) - SH (Single input) Extension cords will vary based on requirements

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST