

# 2800 Machine

# ANY JOB. ANY SIZE. ANY PLACE.



The 2800-G is specifically designed for contractors to provide a smaller designed footprint with an 18hp Briggs & Stratton V-Twin gas engine. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications.\*Also available with Honda engine

- Fold down loading door
- Removable all steel airlock allows for quick access for maintenance
- User friendly 12 VDC electric dashboard
- Clear polycarbonate safety guard allows for easy inspection
- Durable powder coat finish
- Large hopper capacity for less reloading time
- Control panel with engine controls, pressure gauge and air bleed off
- 5 gallon fuel tank with fuel shut off
- Heavy duty Positive Displacement Blower

## AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY



### 65 Years of American Ingenuity



12 VDC Electric Dashboard LED start button / kill switch



18 hp Briggs & Stratton V-Twin Gas Engine \*Also available with 20hp Honda Gas Engine

#### HOPPER CAPACITY

40 cu.ft. (1.13m<sup>3</sup>) Loading made easy with built in adaptable tray

#### WEIGHT/DIMENSIONS

1195lbs / 41"W x 65"D x 73"H 542kg / 99cm x 165cm x 185cm

#### **BLOWER SIZE**

Positive Displacement Blower Blower system yields 135CFM @ 6 PSI

#### AIRLOCK

16" x 12" diameter 40.6cm x 30.5cm diameter 4"(10.16cm) Outlet

#### CONTROL PANEL

Engine controls, pressure gauge & air bleed off

#### **ACCESSORIES**

Machine includes corded remote Optional accessories sold seperately

### OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
	44" Hose Reel	1
KIT-641-12-24K	Wireless Remote	1
2800MK	2800 Maintenance Kit	1



**Dual Agitators** material flow



Positive Displacement Designed for constant Blower w/135 CFM @ 6PSI

#### MATERIAL PRODUCTION RATE

#### Cellulose

**Fiberglass** 

3600 (1633)\*

2100 (953)\*

\*Lbs./hr. (kg/hr.) rating with 150 ft. (45.8m) of 4" (7.6cm) hose at 16ft. (4.8m) elevation.

### 2800 PACKAGE

Part Numbers	Description	QTY
2800-G	2800 Gas Machine	1
H330	4" x 50' Hose	3
340	4" Clamps	5
381	4" Connector	2

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST