

325 Machine

ANY JOB. ANY SIZE. ANY PLACE.



The 325 is preferred as an economical machine for the professional contractor or do-it-yourself rental market. Designed for low maintenance, rugged performance, and medium production. Capable of blowing all major brands of cellulose to the manufacturer specifications.

- Lightweight machine
- User friendly electric dashboard
- Small 8 amp / 2 stage blower
- Rugged pneumatic tires
- Durable powder coat finish

AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY



Electric Dashboard

LED start button - Audible alarm
Motor reset button - Fuse protection
Recessed power supply



Dual Agitators
Designed for constant
material flow

MATERIAL PRODUCTION RATE

Cellulose

900 (408)*

*Lbs/hr (kg/hr) rating with 100 ft. (30.5m)
of 2 1/2" (6.4cm) hose at 10ft (3.1m) elevation.

POWER REQUIREMENT

Single input, 15amp / 120V / 60Hz CSA/CUL/UL

HOPPER CAPACITY

9 cu.ft. (.25m³)

WEIGHT/DIMENSIONS

145lbs / 28.5"W x 29.5"D x 49.5" H
66kg / 72cm x 75cm x 126cm

BLOWER SIZE

8 amp / 2-Stage (120 volt)
Blower system yields 104CFM @ 2 PSI

AIRLOCK

8" x 8" diameter
20.3cm x 20.3cm diameter
2.5"(6.4cm) Outlet

ACCESSORIES

Machine includes corded remote
Optional accessories sold separately

325 PACKAGE

Part Numbers	Description	QTY
325-R	325 Machine	1
H318	2.5" x 50' Hose	2
339A	2.5"-3" Clamps	3
379	2.5" Connector	1
EXTCORD-B	100' Extension Cords	1

OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
328	36" Hose Reel	1
325MK	325 Maintenance Kit	1

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST

Note: Manufacturer's product brand, density and variable blowing conditions will affect production rate.