



KRENDL

The Innovator in Insulation Equipment

5200 Machine Electric

ANY JOB. ANY SIZE. ANY PLACE.

Maximize your production with a 5200. Designed for low maintenance and high production, while offering rugged performance. Capable of blowing all types and brands of loosefill insulation to the manufacturer's specifications. The 5200 Electric is for the busy professional to be used in production facilities for manufactured housing.

- Fold down loading door
- Removable all steel airlock allows for quick access for maintenance
- Durable powder coat finish
- Large hopper capacity for less reloading time
- Heavy duty Positive Displacement Blower

***Also available in Diesel**

AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY

KRENDL MACHINE COMPANY • 1201 SPENCERVILLE RD. DELPHOS, OH 45833 • 800.459.2069 • F 419.695.9301



Positive Displacement Blower
w/220 CFM @ 5PSI (Electric)

POWER REQUIREMENTS

240v Single Phase
480v 3 Phase
240v 3 Phase
208v 3 Phase

HOPPER CAPACITY

70 cu.ft. (1.98m³)

Loading made easy with built in adaptable tray



Multiple Agitators
Designed for Constant Material Flow

WEIGHT/DIMENSIONS (Electric)

2123lbs / 51" W x 82" D x 83" H
963kg / 129 cm x 208 cm x 211 cm

BLOWER SIZE

Positive Displacement Blower
Blower system yields 250CFM @ 6 PSI

MATERIAL PRODUCTION RATE

Cellulose

5200 (2359)*

Fiberglass

2300 (1043)*

*Lbs/hr (kg/hr) rating with 150 ft. (45.8m)
of 4" (7.6cm) hose at 16ft (4.8m) elevation.

AIRLOCK

18" x 14" diameter
45.7cm x 35.5cm diameter
4" (10.16cm) Outlet

ACCESSORIES

Machine includes corded remote
Optional accessories sold separately

5200 PACKAGE

Part Numbers	Description	QTY
5200*	5200 Model	1
H330	4" x 50' Hose	3
340	4" Clamps	5
381	3" Connector	2
*Part number will vary based on power source		

OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
ST329	44" Hose Reel	1
KIT-641-12-24K	Wireless Remote	1
52003E-MK	5200 Maintenance Kit	1

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST

Note: Manufacturer's product brand, density and variable blowing conditions will affect production rate.