

575 Machine

The Innovator in Insulation Equipment

ANY JOB. ANY SIZE. ANY PLACE.



The 575 will out perform and outlast the competition. The 575 is an economical machine for the professional contractor. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications.

- Fold down loading door
- Removable all steel airlock allows for quick access for maintenance
- Lightest machine in its class
- User friendly electric dashboard
- Clear polycarbonate safety guard allows for easy inspection
- Durable powder coat finish
- Double 14 amp / 2 Stage blowers
- Polyurethane flat free tires
- Built in tool holder

AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY



65 Years of American Ingenuity



Electric Dashboard

LED start button - Digital hourmeter Digital voltmeter - Variable blower speed controls Recessed power supply



Dual Agitators Designed for constant material flow



Clear Safety Guard Allows for easy inspection

POWER REQUIREMENT

Single input, 30 amp 240V / 60Hz CSA/CUL/UL
Double input, 30/15 amps each / 120V / 60Hz CSA/CUL/UL
Triple input, 15 amps each / 120V / 60Hz CSA/CUL/UL
International - Double input, 230V / 50Hz CE

HOPPER CAPACITY

14 cu.ft. (.39m³) Loading made easy with built in adaptable tray

WEIGHT/DIMENSIONS

382lbs / 40.5"W x 31.5"D x 63"H 173kg / 103cm x 80cm x 160cm

BLOWER SIZE

14 amp / 2-Stage (120V) Double blower system - Each yields 140CFM @ 3.5 PSI

AIRLOCK

14" x 10" diameter 35.5cm x 25.4cm diameter 3"(7.6cm) Outlet

ACCESSORIES

Machine includes corded remote Optional accessories sold seperately

MATERIAL PRODUCTION RATE

Cellulose

Fiberglass

2600-2800 (1179-1270)* 800-1000(363-454)*

*Lbs/hr (kg/hr) rating with 150 ft. (45.8m) of 3" (7.6cm) hose at 16ft (4.8m) elevation.

575 PACKAGE

Part Numbers	Description	QTY
0575SH*	575 Machine 240V	1
H319	3" x 50' Hose	3
339A	2 ½"-3" Clamps	5
380	3" Connector	2
EXTCORD-H*	100' Extension Cord	1

OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
328	36" Hose Reel	1
KIT-641-12-24K	Wireless Remote	1
575MK	575 Maintenance Kit	1

*DL (Double input) - SH (Single input) - TL (Triple input) Extension cords will vary based on requirements

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST