

6000T Machine

The Innovator in Insulation Equipment

ANY JOB. ANY SIZE. ANY PLACE.



Wall spray recycle hood

Maximize your production with a 6000T. Designed for low maintenance and high production, while offering rugged performance. Capable of blowing all types and brands of loosefill insulation to the manufacturer's specifications.

- Dual upper agitators for maximum conditioning and mixing of insulation.
- Heavy duty #60 nickle plated chain drive system.
- Fold down loading door
- Durable powder coat finish
- Extra large hopper capacity for less reloading time & easy loading (holds up to 110 cu ft)
- Heavy duty Positive Displacement Blower
- User friendly 12 VDC electric dashboard

*Optional 7800 watt generator to power 120 VAC outlets

*Optional recycle hood & vacuum available for wall spray applications

AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY



65 Years of American Ingenuity



Wall Spray Recycle Hood Designed w/filter bag & slidegate for dust fee environment



Optional 7800 watt Generator Powers auxilary 120VAC outlets Positive Displacement Blower w/250 CFM @ 6PSI



Speed Reducer powers the drive system



Dual upper & Multiple lower Agitators
Designed for maximum conditioning
and material flow

HOPPER CAPACITY

110 cu.ft. (3.11m³) Loading made easy with built in adaptable tray

WEIGHT/DIMENSIONS

2250lbs / 72"W x 75"D x 83"H 1021kg / 183cm x 191cm x 211cm

BLOWER SIZE

Positive Displacement Blower Blower system yields 250CFM @ 6 PSI

AIRLOCK

18" x 14" diameter 45.7cm x 35.5cm diameter 4"(10.16cm) Outlet

ACCESSORIES

Machine includes corded remote Optional accessories sold seperately

MATERIAL PRODUCTION RATE Cellulose Fiberglass

5200 (2359)*

2300 (1043)*

*Lbs/hr (kg/hr) rating with 150 ft. (45.8m) of 4" (7.6cm) hose at 16ft (4.8m) elevation.

6000T PACKAGE

Part Numbers	Description	QTY
6000TG-A	6000T PTO Machine	1
H330	4" x 50' Hose	3
340	4" Clamps	5
381	4" Connector	2

OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
ST329	44" Hose Reel	1
KIT-641-12-24k	Wireless Remote	1

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST